

Hydro Balance



32 OZ.



PVE 32

POLYVINYL ETHER REFRIGERATION LUBRICANT

For Use in Systems Requiring Polyvinyl Ether Lubricant

- Compatible with all HFC refrigerants
- Excellent lubricity for greater wear protection
- Does not hydrolyze to form acid
- Meets or exceeds OEM specifications
- Exceptional resistance to capillary tube blockage

H-PVE3232

WARNING: Suspected of damaging fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye protection.



FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation develops or persists, get medical attention. IF INHALATION: Remove person to fresh air if adverse effects are observed. IF SKIN CONTACT: Wash with soap and water. If skin irritation occurs, get medical attention. IF INGESTED: Do not induce vomiting. Rinse mouth. Get medical attention if symptoms occur.

ISO VG 32

OEM APPROVED



Made in U.S.A.
HYDRO-BALANCE CORP.
519 Huffines Blvd., Lewisville, TX U.S.A.
(800) 527-5166 (972) 394-9422
www.HydroBalance.com

HYDRO-BALANCE® PVE 32 is a new generation polyvinyl ether compressor lubricant for use with HFC refrigerants. Polyvinyl ether based lubricants are inherently resistant to hydrolysis which provides superiority over polyol esters (POE).

HYDRO-BALANCE PVE 32 is for use in systems requiring ISO VG 32 polyvinyl ether lubricant and replaces FVC32D. Where approved by the OEM, HYDRO-BALANCE PVE 32 is also suitable for systems requiring ISO VG 32 polyvinyl ether lubricant.

Always consult equipment/compressor manufacturer for proper lubricant selection.

Refrigeration lubricants absorb moisture from the air. This container was packaged under dry nitrogen to preserve product integrity. Always keep container tightly closed unless dispensing.







Store locked up. Dispose of contents and container in accordance with all local, regional, and national regulations.

Lube Chart on Back

Hydro-Balance Lubes



POLYOL ESTER LUBRICANTS

- Excellent lubricating properties over a wide temperature range
- OEM Approved
- Specially formulated for use with HFC refrigerants

DESCRIPTION	ITEM #	CONTAINER	VISCOSITY SUS @ 100°F	ISO VISCOSITY GRADE	REPLACES
ISO 32, SYNTHETIC ESTER	P-3232 P-3201	32-OUNCE 1-GALLON	150 SUS		RL 32H EAL 32
ISO 32 3MAF, SYNTHETIC ESTER (COPELAND APPROVED)	P-323MAF32 P-323MAF01	32-OUNCE 1-GALLON	150 SUS		RL32 3MAF
ISO 68, SYNTHETIC ESTER	P-6832 P-6801	32-OUNCE 1-GALLON	300 SUS		SW 68 RL 68HB
ISO 68S, SYNTHETIC ESTER	P-E6832 P-E6801	32-OUNCE 1-GALLON	300 SUS		ICEMATIC E68 RL 68H EAL 68
ISO 100, SYNTHETIC ESTER	P-E10032 P-E10001	32-OUNCE 1-GALLON	500 SUS		ICEMATIC E100 RL100E
ISO 220, SYNTHETIC ESTER	P-22032 P-22001	32-OUNCE 1-GALLON	1100 SUS		SW 220 RL 220HC +




MINERAL LUBRICANTS

- High quality naphthenic based lubricants
- OEM approved
- Compatible with CFC and HCFC refrigerants
- Moisture and wax free
- Filtered to 1 micron for high purity



MINERAL REFRIGERATION OIL #3 (COPELAND APPROVED)	H-2301 H-2305	1-GALLON 5-GALLON PAIL	150 SUS		3GS, C-3, R0-15, WF 32
MINERAL REFRIGERATION OIL #4	H-2401 H-2405	1-GALLON 5-GALLON PAIL	300 SUS		4GS, C-4, R0-30, WF 68

ALKYLBENZENE LUBRICANTS

- High quality reliable lubrication
- High solubility ~ Low foaming ~ Low floc point
- Excellent thermal stability
- OEM approved
- Compatible with CFC & HCFC refrigerants and mineral oils

Z-150 ALKYLBENZENE REFR. OIL	Z-150 01	1-GALLON	150 SUS		ZEROL 150 RF 150 AB 150 ROYCO 2032
Z-200CX ALKYLBENZENE REFR. OIL (COPELAND APPROVED)	Z 200 01	1-GALLON	200 SUS		ZEROL 200TD AB 200A
Z-300 ALKYLBENZENE REFR. OIL	Z 300 01	1-GALLON	300 SUS		ZEROL 300 AB 300

SPECIALTY PRODUCTS

DUAL-PURPOSE VACUUM PUMP OIL	H-2601 H-2600	1-GALLON 32-OUNCE			VIRGINIA KMP NU-CALGON JB, ROBINAIR, ETC.
PVE 32 POLYVINYL ETHER	H-PVE3201 H-PVE3232	32-OUNCE			VG 32 PVE
PVE 68 POLYVINYL ETHER	H-PVE6801 H-PVE6832	32-OUNCE			VG 68 PVE
LUBRI-TECT™ NEUTRALIZES, SCAVENGES, PREVENTS ACID AND MOISTURE IN A/C AND REFRIGERATION SYSTEMS	H-3702	2.4 FL OZ			ACID AWAY ACID SCAVENGER ACID NEUTRALIZERS