


Hydro Balance



32 oz.

1 Gal.

HYDRO-BALANCE



EVER-CLEAN COOLING COIL ANTI-FOULANT

- Continuously Protects Coils From Fouling Caused By Airborne Particulate And Other Contaminants – For Up To 2-3 Years
- Contains Preservatives That Protect It From Deterioration Caused By Mold And Bacterial Growth Common In Air Conditioning Units
- Eliminates Foul Odors At Their Source
- Improves Indoor Air Quality (IAQ)

CAUTION: KEEP OUT OF REACH OF CHILDREN. SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY AND FIRST AID STATEMENTS

H-9901, H-9932

H-9901, H-9932

CAUTION: Splash goggles are recommended.

FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation develops or persists: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

Contains [CAS]:Acrylic polymer(s) [non-hazardous], Dipropylene glycol methyl ether [34590-94-8].



Made in U.S.A.
HYDRO-BALANCE CORP.
519 Huffines Blvd., Lewisville, TX U.S.A.
(800) 527-5166 (972) 394-9422
www.HydroBalance.com

LONG LASTING

SPRAYER REFILL

USE FULL STRENGTH
(Do not dilute)

Read entire label and Safety Data Sheet before use. Use only according to directions. Shake well before use. For best results apply with a garden or hand type sprayer adjusted to a fine mist. Use enough EVER-CLEAN to dampen entire coil surface. Coil must be thoroughly cleaned and DRY before application. PRE-CLEAN is ideal for cleaning coil prior to treatment as it is manufactured to be compatible with EVER-CLEAN. Drying of coil can be accelerated by running the fan only. Allow at least 30 minutes for EVER-CLEAN to cure before putting system back on line. Clean spraying equipment with water.

DIRECTIONS FOR USE:

1. Shake well before use
2. Clean and dry coil thoroughly.
3. If possible spray coil from intake side and leave air flow on to aid complete coil penetration. Use a fine mist and spray lightly to avoid bridging the coating between fins.
4. Allow at least 30 minutes cure time before putting system back on line.
5. EVER-CLEAN is a water based product. Keep it out of contactors, motors, etc.

