



HYDRO-BALANCE



## H-ES01

H-ES01

DANGER: May be fatal if swallowed and enters airways.



**DDORLESS** 

**VON-CHLORINATED** 

FIRST AID: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation develops or persists: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POI-SON CENTER/doctor if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.



Made in U.S.A. HYDRO-BALANCE CORP. 519 Huffines Blvd., Lewisville, TX U.S.A. (800) 527-5166 (972) 394-9422 www.HydroBalance.com

## ENVIRO-SOLV DEGREASING SOLVENT

**DANGER:** MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. FOR PROFES-SIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. SEE PRECAUTIONS ON BACK PANEL.

FULLY COMPLIES WITH (LVP) EXEMPTION SET BY THE CALIFORNIA AIR RESOURCES BOARD FOR V.O.C.'S IN CONSUMER PRODUCTS. THIS PRODUCT DOES NOT CONTAIN SARA TITLE III SECTION 313 REPORTABLE INGREDIENTS.

**ENVIRO-SOLV DEGREASING SOLVENT** is ideal for use by technicians in H.V.A.C., refrigeration and electrical industries. It will safely and effectively remove oil, grease and greasy grime from mechanical parts, sheet metal, coils, switches, motor armatures, etc.

**ENVIRO-SOLV DEGREASING SOLVENT** is a unique, full-strength solvent that combines cleaning effectiveness with personal safety and environmental concerns. Unlike commonly used solvents that contain chlorinated hydrocarbons, this product contains no suspected human cancer causing material or toxic substances as defined by SARA Title III, Section 313.

Due to its slow evaporation rate, this product is excellent for use in dip tanks. It evaporates completely, residue free, at about the same rate as water. If desired, accelerated evaporation can be achieved by forced air drying or wiping dry with a clean cloth.

## ENVIRO-SOLV DEGREASING SOL-

**VENT** has a flash point of 175° F (minimum) and is classified as a combustible liquid. Do



not use near fire or flame. If this product is accidenspilled, it is not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA).

**DIRECTIONS FOR USE:** Apply generously by swabbing or brushing. Parts can be immersed in the solvent and a brush used to assist in cleaning heavily caked-on-greases. Drying can be accelerated by used forced air or wiping with rags.

Store locked up. Dispose of contents and container in accordance with all local, regional, and national regulations.