

**Hydro  
Balance**



1 GAL.

HYDRO-BALANCE



COPELAND APPROVED

Z200 01

**CAUTION:** KEEP OUT OF REACH OF CHILDREN. FOR PROFESSIONAL USE ONLY. Read Safety Data Sheet and entire label before use.

**FIRST AID:** Wash skin contact thoroughly with soap and water. Flush eyes with water for 15 minutes. Get medical attention if irritation develops. Avoid repeated and prolonged contact.



Made in U.S.A.  
**HYDRO-BALANCE CORP.**  
519 Huffines Blvd., Lewisville, TX U.S.A.  
(800) 527-5166 (972) 394-9422  
[www.HydroBalance.com](http://www.HydroBalance.com)

# Z-200cX

## ALKYLBENZENE REFRIGERATION OIL VISCOSITY GRADE 46

### @100°F 200 SUS

MEETS SPECIFICATIONS OF MANY COMPRESSOR  
AND EQUIPMENT MANUFACTURERS

**Contents approved by Copeland Compressor**

Excellent Compatibility • Low Floc Point  
Reliable Lubrication • High Solubility  
Low Foaming • Excellent Thermal Stability

Z-200CX is recommended for use with refrigerants R-401a/R-401b and R-402a/R402-b, as well as other HCFC and CFC refrigerants in field service and retrofit applications. Z-200CX can also be used for the initial flush in HFC retrofits. ALWAYS FOLLOW THE EQUIPMENT MANUFACTURER'S RECOMMENDATION FOR SELECTION.

**NOTE:** Refrigeration lubricants absorb moisture from air which may be harmful to equipment. Keep container tightly closed when not dispensing.









Lube Chart on Back

# Hydro-Balance Lubes



## POLYOL ESTER LUBRICANTS

- Excellent lubricating properties over a wide temperature range
- OEM Approved
- Specially formulated for use with HFC refrigerants

DESCRIPTION	ITEM #	CONTAINER	VISCOSITY SUS @ 100°F	ISO VISCOSITY GRADE	REPLACES
ISO 32, SYNTHETIC ESTER	P-3232 P-3201	32-OUNCE 1-GALLON	150 SUS		RL 32H EAL 32
ISO 32 3MAF, SYNTHETIC ESTER (COPELAND APPROVED)	P-323MAF32 P-323MAF01	32-OUNCE 1-GALLON	150 SUS		RL32 3MAF
ISO 68, SYNTHETIC ESTER	P-6832 P-6801	32-OUNCE 1-GALLON	300 SUS		SW 68 RL 68HB
ISO 68S, SYNTHETIC ESTER	P-E6832 P-E6801	32-OUNCE 1-GALLON	300 SUS		ICEMATIC E68 RL 68H EAL 68
ISO 100, SYNTHETIC ESTER	P-E10032 P-E10001	32-OUNCE 1-GALLON	500 SUS		ICEMATIC E100 RL100E
ISO 220, SYNTHETIC ESTER	P-22032 P-22001	32-OUNCE 1-GALLON	1100 SUS		SW 220 RL 220HC+




## MINERAL LUBRICANTS

- High quality naphthenic based lubricants
- OEM approved
- Compatible with CFC and HCFC refrigerants
- Moisture and wax free
- Filtered to 1 micron for high purity


MINERAL REFRIGERATION OIL #3 (COPELAND APPROVED)	H-2301 H-2305	1-GALLON 5-GALLON PAIL	150 SUS		3GS, C-3, R0-15, WF 32
MINERAL REFRIGERATION OIL #4	H-2401 H-2405	1-GALLON 5-GALLON PAIL	300 SUS		4GS, C-4, R0-30, WF 68

## ALKYLBENZENE LUBRICANTS

- High quality reliable lubrication
- High solubility ~ Low foaming ~ Low floc point
- Excellent thermal stability
- OEM approved
- Compatible with CFC & HCFC refrigerants and mineral oils

Z-150 ALKYL BENZENE REFR. OIL	Z-150 01	1-GALLON	150 SUS		ZEROL 150 RF 150 AB 150 ROYCO 2032
Z-200CX ALKYL BENZENE REFR. OIL (COPELAND APPROVED)	Z 200 01	1-GALLON	200 SUS		ZEROL 200TD AB 200A
Z-300 ALKYL BENZENE REFR. OIL	Z 300 01	1-GALLON	300 SUS		ZEROL 300 AB 300

## SPECIALTY PRODUCTS

DUAL-PURPOSE VACUUM PUMP OIL	H-2601 H-2600	1-GALLON 32-OUNCE			VIRGINIA KMP NU-CALGON JB, ROBINAIR, ETC.
PVE 68 POLYVINYL ETHER	H-PVE6832	32-OUNCE			VG 68 PVE
LUBRI-TECT™ NEUTRALIZES, SCAVENGES, PREVENTS ACID AND MOISTURE IN A/C AND REFRIGERATION SYSTEMS	H-3702	2.4 FL OZ			ACID AWAY ACID SCAVENGER ACID NEUTRALIZERS