

Mineral Refrigeration Oil #3

LUBRICANT



VISCOSITY



KEY FEATURES

- Viscosity 150 SUS (ISO VG 32) Replaces 3GS
- OEM Approved, Wax free, Highest quality available
- Refined from select naphthenic base oils
- For use with CFC and HCFC refrigerants
- Long-term, trouble-free service, Excellent low temperature properties



Part #	Product	QTY	Size
H-2301	Mineral Oil	4	1 Gal Bottles
H-2305	Mineral Oil	1	5 Gal. Pail

This package contains RO-15, manufactured by Calumet Lubricants Co., and meets the specifications of most equipment manufacturers including: **Copeland, Carrier, Carlyle, Danfoss, Embraco, Trane, General Electric, Americold, Bristol**

Application Recommendations: Mineral Refrigeration Oils are recommended for use with CFC, HCFC, and ammonia refrigerants. Do NOT use in systems with HFC refrigerants such as R134a and R410a. ALWAYS FOLLOW THE EQUIPMENT MANUFACTURER'S RECOMMENDATION FOR SELECTION. If none is available, use the following as a guide:

For refrigerants 11, 12 and 113 with evaporator temperatures above -20°F, use 150 SUS or 300 SUS; below -20°F, use 150 SUS.

For Refrigerants 13, 22, 114, 502 ethane, propane and isobutane, use 150 SUS.

For ammonia with evaporator temperatures above -20°F, use 300 SUS or 500 SUS; below -20°F, use 150 SUS.

CAUTION: Keep out of reach of children. For professional use only. Consult Material Safety Data Sheet and read entire label before use.

FIRST AID: Wash skin contact thoroughly with soap and water. Flush eyes with water for 15 minutes. Get medical attention if irritation develops. Avoid repeated and prolonged contact.

NOTE: Refrigeration lubricants absorb moisture from air which may be harmful to equipment. Keep container tightly closed when not dispensing.