

Mineral Refrigeration Oil #4

LUBRICANT



VISCOSITY



KEY FEATURES

Viscosity 300 SUS (ISO VG 68) Replaces 4GS and C-4

OEM Approved, Wax free, Highest quality available

Refined from select naphthenic base oils

For use with CFC and HCFC refrigerants

Long-term, trouble-free service, Excellent low temperature properties



Part #	Product	QTY	Size
H-2301	Mineral Oil	4	1 Gal Bottles

This package contains RO-30, manufactured by Calumet Lubricants Co. It is made from the highest quality materials available and meets the specifications of most equipment and compressor manufacturers for applications requiring a 300 SUS (ISO VG 68) mineral compressor lubricant.

Consult equipment manufacturer for specific recommendations.

Application Recommendations: Mineral Refrigeration Oils are recommended for use with CFC, HCFC, and ammonia refrigerants. Do NOT use in systems with HFC refrigerants such as R134a and R410a. **Always Follow The Equipment Manufacturer's Recommendation For Selection.** If none is available, use the following as a guide:

- For refrigerants 11, 12 and 113 with evaporator temperatures above -20°F, use 150 SUS or 300 SUS; below -20°F, use 150 SUS.
- For Refrigerants 13, 22, 114, 502 ethane, propane and isobutane, use 150 SUS.
- For ammonia with evaporator temperatures above -20°F, use 300 SUS or 500 SUS; below -20°F, use 150 SUS.

CAUTION: Keep out of reach of children. For professional use only. Consult Material Safety Data Sheet and read entire label before use.

FIRST AID: Wash skin contact thoroughly with soap and water. Flush eyes with water for 15 minutes. Get medical attention if irritation develops. Avoid repeated and prolonged contact.

NOTE: Refrigeration lubricants absorb moisture from air which may be harmful to equipment. Keep container tightly closed when not dispensing.