

# Hydro-Treat™

## Color Coded Cooling Water Treatment



### KEY FEATURES

**Helps keep surfaces free of insoluble materials**

**Multi-functional water treatment containing no chromates or heavy metals, Environmentally safe**

**Helps control corrosion by forming a protective molybdenum film on metal surfaces**

**Works with color coded visual test strips**

Part #	Product	QTY	Size
H-901	Water Treatment	4	1 Gal Bottle
H-905	Water Treatment	1	5 Gal Pail



Hydro-Treat utilizes polymerphosphonates for scale control; corrosion control is maintained by the formation of a protective molybdenum film on metal surfaces. Hydro-Treat also contains dispersants and peptizing agents to keep heat transfer surfaces free of insoluble materials such as silt, sand and airborne particles.

Hydro-Treat makes cooling water treatment dosage a simple matter of matching colors. Addition of Hydro-Treat will turn circulating water blue. Treatment levels are easily maintained by using Hydro-Treat color coded visual test strips.

**Directions For Use:**

Hydro-Treat may be fed either by the use of plastic feeding pumps or in slug doses. Normal dosage of Hydro-Treat will range between 200 and 300 ppm in circulating water. (Approximately 1 quart per 1000 gallons of water.)

**Control:** Use Hydro-Treat color coded test strips to match color of circulating water. Over treatment is not harmful. Be sure Hydro-Treat is thoroughly mixed in circulating water before testing. Maintain adequate bleed off rate. Use Hydro-Cide for control of algae and microbiological fouling.

**FIRST AID:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation develops or persists: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

Contains [CAS]: Soluble Molybdenum Compound [7631-95-0].



**HYDRO-BALANCE CORPORATION**  
 519 HUFFINES BLVD. LEWISVILLE, TX 75056  
 (800) 527-5166 | (972) 394-9422  
 HydroBalance.com

