

H-9932

Ever-Clean Cooling Coil Anti-Foulant



ADY TO USA

KEY FEATURES

Continuously Protects Coils From Fouling Caused By Airborne Particulate And Other Contaminants – For Up To 2-3 Years

Contains Preservatives That Protect It From Deterioration Caused By Mold And Bacterial Growth Common In Air Conditioning Units

Eliminates Foul Odors At Their Source

Improves Indoor Air Quality (IAQ)

Improves Indoor Air Quality (IAQ)

Part #	Product	QTY	Size
H-9932	Anti-Foulant	12	1 32 oz. Spray Bottle
H-9901	Anti-Foulant	4	1 Gal Bottle



Read entire label and Safety Data Sheet before use. Use only according to directions. Shake well before use. For best results apply with a garden or hand type sprayer adjusted to a fine mist. Use enough EVER-CLEAN to dampen entire coil surface. Coil must be thoroughly cleaned and DRY before application. PRE- CLEAN is ideal for cleaning coil prior to treatment as it is manufactured to be	CAUTION: Splash goggles are recommended.
compatible with EVER-CLEAN. Drying of coil can be accelerated by running the fan only. Allow at least 30 minutes for EVER-CLEAN to cure before putting system back on line. Clean spraying equipment with water. Directions For Use: 1. Shake well before use 2. Clean and dry coil thoroughly.	FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation develops or persists: Get medical advice/attention.IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.
3. If possible spray coil from intake side and leave air flow on to aid complete coil penetration. Use a fine mist and spray lightly to avoid bridging the coating between fins.	Contains [CAS]:Acrylic polymer(s) [non-hazardous], Dipropylene glycol methyl ether [34590-94-8].
4. Allow at least 30 minutes cure time before putting system back on line.	

 EVER-CLEAN is a water based product. Keep it out of contactors, motors, etc.





HYDRO-BALANCE CORPORATION 519 HUFFINES BLVD. LEWISVILLE, TX 75056 (800) 527-5166 | (972) 394-9422 HydroBalance.com

