

Cold Pipe Insulating Spray



KEY FEATURES

Use On: Copper, Black Iron, Stainless Steel, Galvanized, Brass and PVC Pipe

Stops Sweating of Cold Pipes

Use To Prevent Drip Damage

Part #	Product	QTY	Size
H-CP18	Cold Pipe Spray	12	18 oz. Can



Shake Well Before Use

Cold Pipe Insulating Spray is a convenient, ready-to-use spray-on pipe insulator. Dries to a hard white coating which can be painted or primed when dry. Prevents sweating and dripping on cold water pipes, refrigeration lines, condensers, air conditioning lines, and other cold surfaces. Insulates water tanks, metal gutters, ducts and toilet tanks. Fan spray application provides an excellent method of repairing wrap around type insulation. Easy to apply to hard to reach areas. Expanding spray conforms to irregularly shaped surfaces.

Directions For Use:

Remove dust and loose dirt from surface to be sprayed by wiping with clean, dry cloth. Protect surrounding are from overspray. Shake can vigorously. Continue shaking for one minute and occasionally during use. For proper adhesion apply only to dry surfaces. Hold can 8-10" from surface. Apply with a sweeping motion using several thin coats. Allow each coat to dry thoroughly for several minutes before applying a new coat. If product runs, can is too close to surface.

WARNING: Flammable Aerosol. Contains gas under pressure; May explode if heated. May cause respiratory irritation, drowsiness or dizziness. Causes skin and serious eye irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wear protective gloves and eye protection. Wash hands thoroughly after handling.

FIRST AID: If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing dust, fumes or mist. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Dispose of contents and container in accordance with local, state, and national regulations.

WARNING: This product can expose you to chemicals including Dichloromethane, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Methylene Chloride (75-09-2), Propane/n-Butane (68476-86-8), Acrylic Polymer (N/A), Hexadecenoic Acid (57-10-3), Octadecanoic acid (57-11-4).

HMS RATINGS: Health - 2, Flammability - 2, Re-activity - 0, Personal - B.

