

# POE32<sup>3MAF</sup>

## Synthetic Polyol-Ester Refrigeration Lubricant

LUBRICANT



VISCOSITY



### KEY FEATURES

**For Use with Environmentally Sound HFC Refrigerants**

**Excellent Lubricating Properties Over a Wide Temperature Range**

**Superior Corrosion Resistance, Plus Excellent Oxidative and Hydrolytic Stability**

**Good Load Carry Capabilities & Excellent Retrofit Capabilities**

Part #	Product	QTY	Size
P-323MAF01	Refrigeration Oil	4	1 Gal Cans
P-323MAF05	Refrigeration Oil	1	5 Gal Pail



### Hydro-Balance ISO Series

Polyol-Ester based refrigeration lubricants are specifically formulated for use with environmentally friendly HFC refrigerants. They are also suitable with HCFC and CFC refrigerants which make them suitable for many applications.

### Typical Compressor Applications

ISO 32 is for use with systems requiring ISO Viscosity Grade 32 polyol ester lubricant.

Contents of this container are manufactured by leading producers of Polyol-Ester refrigeration lubricants and meet the specifications of many equipment and compressor manufacturers. Always consult your manufacturer for specific applications.

### Health & Safety

Avoid prolonged or repeated contact with skin or clothing. If product gets in eyes, flush with water for 15 minutes. If irritation persists, consult a physician. Wash hands with soap and water after use. Read entire label and Safety Data Sheet before use.

**Note:** Refrigeration lubricants absorb moisture from the air. This container is packaged under dry nitrogen to maintain product integrity. Keep container tightly sealed until time of use and when not dispensing.